



6" GATOR WRAP TYP.
AT MANHOLE BARREL
JOINTS

EACH MANHOLE, CATCH BASIN OR PIPE JOINT SHALL BE SEALED WITH AN EXTERNAL RUBBER SLEEVE SIMILAR TO THE INFI-SHIELD GATOR WRAP AS MANUFACTURED BY SEALING SYSTEMS, INC. (763-478-5027). THE SEAL SHALL BE MADE OF A STRETCHABLE, SELF SHRINKING, INTRA-CURING HALOGENATED BASED RUBBER WITH A MINIMUM THICKNESS OF 30 MILS. THE BACK SIDE SHALL BE COATED WITH A CROSS-LINKED RE-ENFORCED BUTYL ADHESIVE. THE BUTYL ADHESIVE SHALL BE NON HARDENING SEALANT, WITH A MINIMUM THICKNESS OF 30 MILS. THE SEAL SHALL BE DESIGNED TO STRETCH AROUND THE SUBSTRATE ADHESIVE. THE APPLICATION SHALL FORM A CONTINUOUS RUBBER SEAL THAT APPLIES INWARD PRESSURE ON THE PROTECTED AREA FOR THE LIFE OF THE APPLICATION. THE BUTYL ADHESIVE AND THE INWARD PRESSURE EXERTED ON THE SUBSTRATE WILL PREVENT THE INTRUSION OF WATER AND SOIL THROUGH THE JOINT SECTIONS OF A MANHOLE, CATCH BASIN, OR CONC PIPE.

Sealing Systems, Inc.
9350 County Road 19
Loretto, MN 55357
763-478-2057



MANHOLE DETAIL WITH
INFI-SHIELD AND
GATOR WRAP